



## Siemens LC91KB672B Cooker Hood 90cm Angled Touch Control

<b>Brand</b>	Siemens
<b>EAN Number</b>	
<b>Colour</b>	Stainless Steel
<b>Hood Type</b>	Chimney

Design

- 90 cm wide

- Black
- White electronic display
- Electronic control via Touch control
- Light colour: warm white
- For wall mounted installation
- Designed for suspended or flush ceiling installation

#### Key features

- Touch control for extractor speeds and light
- Boost function
- 3 x LED lights
- softLight with dimmer function
- 1 x metal grease filter cassette
- Grease filter saturation indicator
- Glass filter cover, Steel filter cover
- Rim ventilation

#### Performance/technical information

- Suitable for ducted and re-circulating operation
- For recirculated extraction recirculating kit or CleanAir recirculating kit (accessory) needed
- Extraction rate according to EN 61591  $\varnothing$  15 cm:  
max. Normal use 580 m<sup>3</sup>/h  
Intensive 800 m<sup>3</sup>/h
- Noise level according to EN 60704-3 and EN 60704-2-13 exhaust air:  
Max. normal use: 62 dB(A) re 1 pW (48 dB(A) re 20  $\mu$ Pa sound pressure)  
Intensive: 68 dB(A) re 1 pW (54 dB(A) re 20  $\mu$ Pa sound pressure)
- Additional noise reduction insulation
- 3 power levels and 2 intensive settings
- Power rating: 269 W
- Automatic intensive revert
- 10 minutes
- Noise max. Normal Level: 62 dB\*
- Extractor hose 120 mm

- Dimensions (WxD): 900 x 426 mm
- Dimensions exhaust air (HxWxD): 865-1153 x 900 x 426 mm
- Dimensions recirculating with cleanAir module (HxWxD): 1008-1338 x 900 x 426 mm
- Diameter pipe Ø 150 mm (Ø 120 mm enclosed)
- Light Intensity: 806 lux
- Colour Temperature: 3500 K
- Average Energy Consumption: 39 kWh/year\*
- Energy Efficiency Class: A\*
- Blower Efficiency Class: A\*
- Lighting Efficiency Class: A\*
- Grease Filtering Efficiency Class: B\*